



AERMLED/HO/60/DL

Endurance LED HO Recessed Panel - 600 X 600 Daylight 30W White



Features

High performance maintenance free LED panel.

30W panel outperforms 3x14W T5.

Cool white and warm white options.

White anodised aluminium frame for visual compatibility with ceiling grid.

Low glare and even light distribution for multiple applications.

Panel Pod emergency option.

Panel Pod sensor option.

Surface mounting frame option.

TPb as standard.

LED lifespan L70 40,000 hours.

General Information

Lamp Type	LED
Colour / Finish	White
IP Rating	IP44
Class Protection	2
Internal / External	Internal
Surface / Recessed / Suspended	Recessed
Warranty (Years)	5
CE Mark	Yes
Length (mm)	595
Width (mm)	595
Height (mm)	10
Accessories	AIRMLD/POD/MWS, AIRMLD/POD/3NM/ST, AIRMLD/SMF, AIRMLD/PRK, AIRMLD/SK, AEQTCC/600

Technical Information

Wattage	30W
Lumens Delivered	3838lm
Lm/W	128lm
CRI	Ra 80
CCT	6500K
Input	230V
Hertz	50Hz
Operating Temp	-10°C to 40°C



Technical Data - ETIM 6 - Ceiling-/wall luminaire (EC002892)

Suitable for suspended mounting	Yes
Suitable for ceiling mounting	Yes
Suitable for built-in mounting	Yes
Suitable for surface mounting	Yes
With light source	Yes
Lamp holder	None
Suitable for number of lamps	1
Lamp power at multiwatt	Not applicable
Control gear included	Yes
Nominal voltage	230-230 V
Colour temperature	6500-6500 K
Material housing	Aluminium
Colour housing	White
Suitable for light line configuration	No
Type of grid	None
Length	595 mm
Width	595 mm
Height/depth	10 mm
With movement sensor	No
With light sensor	No
Protection class	II
Degree of protection (IP)	IP44
Ambient temperature	-10-40 °C
Max. system power	30 W
Rated luminous flux acc. IEC 62722-2-1	3838 lm

Colour of light	White
Colour rendering index CRI	80-89

Datasheet generated from <https://www.electrika.com> last updated Monday, June 17, 2019 8:32:59 AM

