



Product Description: Slim-FitCS™ 9W IP44 Colour Switchable Round Low Profile Downlight

The range of Slim-Fit™ low profile downlights are engineered to deliver superior light output and uniformity utilising the latest edge-lit LED technology. At only 20mm deep including bracket, they are an ideal solution where ceiling voids are limited but high lumen output is required.

SKU Code	Wattage	Colour	Lumens	Beam Angle	Finish Colour	SKU Type
AU-PL09CS	9	3000K	800	120	White	Non Dimmable
AU-PL09CS	9	4000K	870	120	White	Non Dimmable
AU-PL09CS	9	6500K	840	120	White	Non Dimmable
AU-PL09CSDA	9	3000K	800	120	White	DALI Dimmable
AU-PL09CSDA	9	4000K	870	120	White	DALI Dimmable
AU-PL09CSDA	9	6500K	840	120	White	DALI Dimmable
AU-PL09CSV	9	3000K	800	120	White	1-10V Dimmable
AU-PL09CSV	9	4000K	870	120	White	1-10V Dimmable
AU-PL09CSV	9	6500K	840	120	White	1-10V Dimmable

Line Drawing

Polar Curve

Colour

Feature & Benefits

Product Specs:

Input Voltage	220~240V AC	Input Frequency	50/60HZ
IP Rating	IP44	Lifetime L70 (hrs)	50000hrs
IK Rating	IK06	Lamp Base	None
Overall Diameter (mm)	150	Height (mm)	22
Product Type	Downlights	Cutout Diameter (mm)	132-135
Operating Temp. (Min) °C	-20°C	Operating Temp. (Max) °C	40°C

Compliance & Approvals:

Warranty:

This product has a warranty period of 5 Years. Warranties may be available on certain products as indicated in the product description. Warranties are valid from the date of purchase. The warranty is invalid in the case of improper use, installation, tampering, removal of the Q.C. date label or installation in an improper working environment or installation. Should this product fail during the warranty period it will be replaced free of charge, subject to the correct installation of the original product and subsequent return of the faulty unit. Aurora does not accept responsibility for any installation costs associated with the replacement of this product and Aurora reserves the right to alter specifications without prior notice.